

THE TURBO-FLOW

Spécifications TURBO-FLOW

| Series / model | 45 | 55 | 70 | 85 |
|----------------|----|----|----|----|
|----------------|----|----|----|----|

Efficiency

| | | | | |
|-----------------------------------|--------|--------|--------|--------|
| Compressor (hp) | 2 | 2,5 | 3,2 | 4 |
| Nominal Heating Capacity (BTU/hr) | 45,000 | 55,000 | 70,000 | 85,000 |
| Heat Exchanger Material | | | | |

Electricity

| | | | | |
|--------------------------------|-----|----|-------------------------------|-----|
| Average Power Consumption (kW) | 2,4 | 3 | 3,6 | 4,2 |
| Electrical Power Supply | | | 208 - 230 V / 1 PHASE / 60 HZ | |
| Circuit Breaker (amps) | 20 | 25 | 40 | 45 |
| Average Running Amp | 11 | 14 | 16 | 18 |

Water Circulation

| | | | | |
|-------------------|--|--|--|-----------------|
| Water Connections | | | | 1 1/2" Diameter |
|-------------------|--|--|--|-----------------|

Physical Aspect

| | | | | |
|--------------|-----|-----|----------------------------|-----|
| Cabinet | | | ABS PLASTIC - U.V. TREATED | |
| Weight (lbs) | 164 | 175 | 208 | 234 |
| Height (in.) | 23 | 23 | 27 | 27 |
| Length (in.) | 37 | 37 | 44 | 44 |
| Width (in.) | 20 | 20 | 20 | 20 |